Cermet II Hygrometer

The hygrometer of choice for the measurement of dew point, temperature, or gaseous moisture applications with a choice of units of measurement or where pressure compensation is required.



Highlights

- Wide measurement range, calibrated -100 to +20°C dew point (-148 to +68°F)
- ±1°C dew point measurement accuracy (±1.8°F)
- Pressure sensor input
- Up to 4 alarm relays
- User selectable units of measurement
- Easy to read display
- Analog and digital outputs

Applications

- Industrial gases
- Dried compressed air
- Welding gases
- Glove boxes
- Medical gases
- High voltage switchgear (SF₆)
- ... and many more



Cermet II Hygrometer

Complete On-Line Dew Point Solution

Cermet II is the intelligent choice for reliable on-line measurement of moisture in virtually any gas, across many applications. Cermet II combines Michell's Advanced Ceramic Moisture Sensor and a monitor unit that can be located up to 1200 m apart (3930 ft). While Cermet II is so simple to use, it has the flexibility to be applied to almost any humidity measurement application. The instrument can display measurement units in °C or °F dew point, ppm_V lb/mmscf or g/m³ across the measurement range -100 to +20°C dew point (-148 to +68°F) at pressures up to 5000 psig. The Cermet II also can accept a pressure signal from a pressure transmitter (optional) providing the means of active pressure compensation for concentration units of measurement.

Cermet II Monitor

The Cermet II Monitor is a fully self-contained display system in a 1/8 DIN panel mounting case that indicates the measured humidity parameter and performs pressure compensation (if required). Cermet II also provides current and digital outputs and two 10 A alarm relays. It is protected to NEMA 12 and can be supplied with an optional front panel providing a NEMA 4X rating. Its operating temperature range is -20 to + 50°C (-4 to + 122°F).

Cermet II Sensor

The Cermet II Sensor uses Michell's Advanced Ceramic Moisture Sensor technology with on-board intelligence. This smart sensor has a measurement range of -100 to $+20^{\circ}$ C dew point (-148 to+68°F) at pressures up to 5000 psig and offers a superior measurement accuracy of better than $\pm 1^{\circ}$ C dew point from -60 to $+20^{\circ}$ C ($\pm 1.8^{\circ}$ F from -76 to $+68^{\circ}$ F). From -100 to -60°C dew point the measurement accuracy is $\pm 2^{\circ}$ C dew point ($\pm 3.6^{\circ}$ F from -148 to -76°F). The on-board processor in the sensor electronics enables excellent performance, reliability and interchangeability of sensors. Cermet II's sensor is designed to perform in harsh environments. Constructed in stainless steel, the sensor is also protected to NEMA 4 and has an operating temperature range of -40 to $+140^{\circ}$ F.

Extreme Flexibility

The dew point of any gas will vary with pressure. When calculating concentration units of measure, Cermet II can compensate for these variations either by using of a live pressure transducer input, or by using a pressure factor input via the instrument front panel.

For control of external devices Cermet II is supplied as with two 10 A, 240 VAC Form 'C', fully user configurable, alarms, standard. These can be set over the full operating range of the instrument, with variable hysteresis for any chosen engineering unit. The alarms can also be configured to flag sensor or cable fault conditions. An additional two alarms can be added if required. Cermet II is supplied with a 4-20 mA output, which is fully configurable for range and scale, standard. In addition, a 2-way RS232 digital signal is provided which gives full data access to the user. Optionally a 0-10 V configurable analog output can be specified, as can an RS485 2-way digital port.

Intrinsically Safe Version

The Cermet II I.S. version adds intrinsic safety barriers with the monitor and the Transmet I.S. transmitter is used. See the Cermet II I.S. data sheet for the ideal solution for measurement and display of gaseous moisture in hazardous areas.

Applications

Cermet II can provide the solution to both energy management and quality assurance in the supply of pure gases and compressed air from heat regenerative, adsorption dryers. The durability of the Advanced Ceramic Moisture Sensor provides long term service in applications such as pipeline drying using vacuum and dry gas purging techniques.



Power station (Peterhead CS)



Technology

The Cermet I.S uses Impedence technology, based on Michell's ceramic sensor.

The Ceramic Sensor is constructed using state of the art thin and thick film techniques. Operation of the sensor depends upon the adsorption of water vapor onto a porous non-conducting "sandwich" between two conductive layers built on top of a base ceramic substrate. The active sensor layer is very thin less than one micron (about 0.00004 inches) and the porous top conductor that allows transmission of water vapor into the sensor is even thinner. Therefore the sensor responds very rapidly to changes in applied moisture, both when being dried (on process start-up) and when called into action if there is moisture ingress into a process.

Despite this extreme sensitivity to changes in moisture content, the Michell Ceramic Moisture Sensor is incredibly rugged due to the nature of its construction. To protect the sensor further against contaminants and pipe swarf it is housed in a protective sintered stainless steel guard. All Michell Ceramic Moisture Sensors give $<\pm 2^{\circ}C (\pm 3.6^{\circ}F)$ dew point accuracy and excellent long-term reliability and stability in process applications.



Order Codes

| Order codes | Product description | |
|-----------------------------------|---|---|
| CT2- {1} - {2} - {3} - {4} - {5} | CERMET II - Full specification On-Line Hygrometer complete with Monitor (1/8 Din), Sensor, 6' Cable, Block, 2 alarms, isolated 4-20mA and RS232 outputs | |
| | | |
| Suffix {1} - Alarms configuration | A2 | Standard 2 alarm relays |
| | A3 | Three alarm relays |
| | A4 | Four alarm relays |
| Suffix {2} - Analog output | mA | Standard 4-20 mA |
| | V | 0-10V |
| Suffix {3} - Digital output | 2 | RS 232 standard output |
| | 4 | RS 485 |
| Suffix {4} - Power supply | AC | Power Supply - 85/265 VAC |
| | DC | Power Supply - 24 VDC |
| Suffix {5} - Sensor cable | 2 | 6' cable with connectors |
| | XXXX | Cable greater than 6' supplied in one single length with connectors - additional price per foot |

Accessories

| Order codes | Product description |
|-------------|--|
| CT2-SEN | Spare sensor for use with CERMET II Hygrometer |
| CSB | Stainless Steel Sample Block for use with Cermet II Sensor - 5/8" UNF thread with 1/8" NPT ports |
| APT-PAN | 3/4"-16 UNF to 5/8" UNF male adapter, stainless steel, (Standard Panametrics thread) |
| APT-GEI | G 1/2" to 5/8" UNF male adapter, stainless steel, (Standard E&H or GEI thread) |
| CT2-IPC | Clear plastic cover for CERMET II Monitor to give environmental protection to NEMA4 (IP66) |
| CT2-CAB | Spare sensor cable, 6' length with connectors |
| EA2-SAM | Easidew Sampler - S/S block with :- filter cartridge (0.3micron), inlet/outlet push fittings, m-valve and PTFE vent tube 0.24" (6mm) dia. For atmospheric or pressure dewpoint measurements (150 psig max). Complete with mounting bracket |
| CT-MON | Replacement Cermet II Monitor |



| Technical Specifications | | | | |
|--|--|--|--|--|
| Sensor | | | | |
| Measurement Range | -100 to +20°C dew point (-148 to +68°F) | | | |
| Accuracy (dew point) | ±1°C from -60 to +20°C dew point (±1.8°F, -76 to +68°F) ±2°C from -100 to -60°C dew point (±3.6°F, -148 to -76°F) | | | |
| Enclosure | Stainless steel | | | |
| Ingress Protection | NEMA 4X | | | |
| Operating Temperature | -40 to +60°C (-40 to +140°F) compensated over -20 to +40°C (-4 to +104°F) | | | |
| Storage Temperature | -40 to +165°F | | | |
| Operating Pressure | From vacuum to 5000 psig (max) | | | |
| Flow Rate | 1 to 5 l/min (2.1 to 10.5 scfh) | | | |
| Gas Velocity | 0 to 10m/sec (0 to 32.8 ft/sec) | | | |
| Process Connection | 5/8" UNF parallel thread | | | |
| Sensor Calibration | Traceable to NIST | | | |
| Analyzer | | | | |
| Measurement Units | °C, °F dew point; ppm _v with user selectable range and resolution; lb/mmscf range dependent on pressure (natural gas); g/m ³ (natural gas). Digital processing and linearization with active or passive pressure compensation | | | |
| Resolution | 0.1 °C from -80 to +20°C dew point (0.18°F, -112 to +68°F) 1°C from -100 to -80°C dew point (1.8°F, -148 to -112°F) | | | |
| Secondary Measurement Variable | Pressure using an optional external transducer over a range of 0 to 4000 psig. Completely user-configurable for any industry standard transducer with an 4-20 mA output. Automatic compensation for ppm_{ψ} lb/mmscf and g/m ³ units. | | | |
| Alarm Relays | Two user adjustable isolated 10A form 'C' rated at 240VAC or 24VDC | | | |
| Outputs: Analog | 4-20 mA as standard (max load 500 Ω) user configurable and scalable R5485 | | | |
| Power Supply | Universal 85 to 265VAC, 50/60 Hz or 95 to 370VDC | | | |
| Operating Conditions | | | | |
| Operating Temperature Monitor: Sensor: | 0 to +50°C (32 to +122°F) -20 to +50°C (-5 to +122°F) | | | |
| Ingress Protection Monitor: | IP54 (NEMA 12) standard (front panel only) IP66 (NEMA4) with optional cover (front panel only) | | | |

| Options | |
|---------------------|--|
| Outputs | |
| Analog: Digital: | 0-20 mA optional (max load 500 Ω) 0-10 V optional (min load 5 K Ω) both user configurable and scalable RS485: provides 2-way communication - full data access to user and total instrument configuration |
| Alarm Relays | 1 or 2 additional 5 A relays (max 4 total) n/o type fully user configurable and adjustable over the full range, full choice of units and sensor fault alarm functions |
| Power Supply | 18 to 36 VAC; 9 to 60 VDC |
| Cable | Standard 6.5 foot (4000 foot max) |

Dimensions









BONDED SEAL Supplied

SENSOR BLOCK

116





40





PANEL CUTOUT

Marketed & Supported By: Toshbro Controls Pvt. Ltd

F-68, Solaris-I, Opp. L&T Gate No. 6, Saki Vihar Road, Powai, Mumbai 400 072. Tel : +91 22 2847 0728. Fax : +91 22 2847 0763 E-Mail : info@toshbrocontrols.com Website : www.toshbrocontrols.com



Sensor:

IP66 (NEMA4)